

NBB75DFIB-P

Isolated BNC chassis connector, feedthrough in black D-shape housing, protruding version (makes locking and unlocking of conventional BNC cable connectors easy)

Neutrik's BNC chassis connectors offer a true 75 Ω design for serial and digital (HD) signals. The machined brass connector body provides an extremely rugged and non-abrasive connection over long term use in a D-shape housing (audio industry standard).



Features & Benefits

- Gold plated cage type center contact
- True 75 Ω design meets the stringent HD requirements
- Isolated panel mount (solves potential grounding problems and prevents common-mode influence with other connections conducted over the same panel ground potential)
- Standard D-shape housing
- Protruding bulkhead jack (makes locking and unlocking of conventional BNC cable connectors easy)
- Color coding possible

New cage type contact

- Closed contact design - extremely robust
- Gold plated cage type clip - best possible shielding and lowest contact resistance



Technical Information [hide](#)

Product

Title NBB75DFIB-P

Connection Type BNC 75 Ω

Gender female

Electrical

Signal Type HD, SDI, Video, AES/EBU, Composit, YUV, RGB, RGBH, RGBHV

Contact resistance ≤ 3 m Ω (inner)

Contact resistance ≤ 2 m Ω (outer)

Dielectric strength 1,5 kVdc

| | |
|-----------------------|--|
| Impedance | 75 Ω |
| Insulation resistance | > 5 GΩ |
| Rated voltage | <50 V |
| VSWR | ≤1.03/>37 dB up to 1 GHz ≤1.05/>32 dB up to 2 GHz ≤1.08/>28 dB up to 3 Ghz |
| Mechanical | |
| Insertion force | < 25 N |
| Lifetime | > 1000 mating cycles |
| Locking device | Bayonett |
| Mounting direction | Front mounting |
| Chassis shape | D |
| Material | |
| Contacts | Brass (CuZn39Pb3), 0.2 μm AuCo (Center contact) |
| Insert | PTFE |
| Shell | Polyacetal (POM) (Insulation Sheell) |
| Shell plating | Optalloy® |
| D-Shape housing | Zinc diecast (ZnAl4Cu1) gal black chrome plating |
| Environmental | |
| Temperature range | -30 °C to +85 °C |

Accessories

DSS-*



MFD



SCDP-*



SCDX



SCCD-W



SCD-W

