

NF2C-B/2

Pair of professional 'Phono Plug' ('RCA' - or 'CINCH' - type) - marked red and black.

Including 2 x 2 strain reliefs for cable O.D. 3.0 mm to 7.3 mm. Additional strain relief for cable O.D. up to 8.0 mm available as accessory.



Features & Benefits

- Makes ground before signal contact and breaks signal before ground
- No more disturbing noise and broken speaker cones
- Precisely machined to our demanding quality standards
- Neutrik unique chuck type strain relief
- Gold plated contacts
- Sleek barrel with soft touch surface and coloured shrink sleeve
- Improved ground solder lug for ease soldering

Technical Information [hide](#)

Product

Title NF2C-B/2

Connection Type Profi

Gender male

Electrical

Capacitance between contacts ≤ 7 pF

Contact resistance $>10G$ m Ω

Dielectric strength 1,5 kVdc

Insulation resistance > 5 G Ω

Rated current per contact depends on mating connector / A

Rated voltage < 50 V

Mechanical

Cable O.D. 3.0 - 7.3 mm

Lifetime > 2000 mating cycles

Wiresize 1,5 mm²

Wiresize 16 AWG

Wiring Solder contacts

Material

Contact plating 5 μ m Au over 5 μ m Ni

Contacts Brass (CuZn39Pb3)

Insert	PBTP 20 % GR
Shell	Brass (CuZn39Pb3)
Strain relief	Polyacetal (POM)
Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 601-14
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

Accessories

CNF-9

