

# NP2RX-B

2 pole 1/4" professional right-angle phone plug, gold contacts, black shell

The heavy duty professional phone plug series improves on the design of the existing C series by offering the thinnest available A-gauge 1/4" plug with unique Neutrik chuck type strain relief on the market. The slimline shell with a width of 14.5 mm meets the most recent requirements for highest density jackfields (15.88mm jack pitch).

The precise machined one-piece tip contact without rivets makes it unique and avoids hook up in a socket or break off the tip.

The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.



## Features & Benefits

- All metal housing eliminates the plastic cover of the predecessor NP\*RCS and improves further durability and EMI protection
- Extra slim 1/4" plug for highest packing density
- Robust diecast shell in stylish design
- Proven chuck type strain relief for reliable cable retention
- Sleek design for best handling convenience
- Precision machined one-piece contacts - avoid hook up of tip contact

## Technical Information [hide](#)

Product	
Title	NP2RX-B
Connection Type	Plug
Gender	male
Electrical	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V
Mechanical	
Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm <sup>2</sup>
Wiresize	18 AWG
Wiring	Solder contacts

---

**Material**

Bushing	Polyacetal (POM) + PU
---------	-----------------------

Contact plating	0.2 µm Au
-----------------	-----------

Contacts	Brass (CuZn39Pb3)
----------	-------------------

Insert	Polyamide (PA 6.6 30 % GR)
--------	----------------------------

Shell	Zinc diecast (ZnAl4Cu1)
-------	-------------------------

Shell plating	Black chromium
---------------	----------------

Strain relief	Polyacetal (POM)
---------------	------------------

**Environmental**

Standard compliance	IEC 60603-11 / EIA RS-453
---------------------	---------------------------

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-20 °C to +65 °C
-------------------	------------------

---

**Accessories**

BPX-\*



BPX-L



HTXP



PXR-\*

