

NP3TT-P-R

4.4 mm (0.173") tiny telephone plug bantam type, solder termination for T+R, hex crimp of S with a standard RG58 crimp tool, red plastic housing, Nickel contacts. Ideal use with TT patch panels.

Features & Benefits

- Designed for pro audio applications
- Robust ergonomic design - long-lasting and dependable
- Standard HEX crimp cable clamp for shield termination and cable retention
- Colored sleeves available for coding and marking



Technical Information [hide](#)

Product

Title NP3TT-P-R

Connection Type Plug

Gender male

Electrical

Contact resistance depends on mating connector mΩ

Dielectric strength 1 kVdc

Insulation resistance > 2 GΩ (initial)

Rated current per contact depends on mating connector A

Rated voltage < 50 V

Mechanical

Cable O.D. 4 - 4.8 mm

Crimp size 5,41 Hex crimp (shield) acc. IEC 60803 (die designation D)

Lifetime > 1000 mating cycles

Wiresize 0,25 mm²

Wiresize 24 AWG

Wiring Solder contacts

Material

Bushing Polyacetal (POM) + PU

Contact plating 2 μm Ni (Su)

Contacts Bronze (CuSn6) (Tip)

Insert Polyamide (PA 6.6 30 % GR)

Shell	Brass (CuZn39Pb3)
Shell plating	Polyamide (6 30% GR) (red)
Environmental	
Standard compliance	MIL-P-642/13
Solderability	Complies with IEC 68-2-20
Temperature range	-20 °C to +65 °C

Accessories

BSTP-*



DIE-R-BNC-PJ



HX-R-BNC

