
地址:广州市番禺区石碁镇海涌路109号 电话:+86 2039966388/39966399 传真:+86 20 39966398/39966389 邮箱:sales@terbly.com

网站: www.terbly.com





产品参数

The ELV-C1/C4-RGB/RGBW/RGBA/DW is a high power, color changing, outdoor linear fixture.

Available in 1'and 4' sections, it offers multiple configuration, including RGB, RGBW, RGBA or DW. Featuring a robust IP66 housing, a multi-voltage switching power supply, and a glare shield, it is the perfect option for any structure that calls for outdoor linear grazing.



ELV-C1/C4-RGB/RGBW/RGBA

LED Source: RGB, RGBW or RGBA

DMX Channel: 3 or 4

Beam Angle: 120 °

Max Fixture Runs: 50'@120V/100'@240V Power Consumption: 20W(1')/80W(4')

Total Lumens: 1' 700lm 4' 2800lm

Efficacy (Im/W): 35Im/W

CRI: >80

Finish: Anodized Brushed Aluminum (Black or White - Special Order Only)

Housing: Aluminum; Clear Polycarbonate Lens Cover

Operating Temperature: -20 ° C ~ 45 ° C

Operating Voltage: 100-277V

Dimming: DMX 512

Fixture Connectors: Integral, 8 Pin Male & Female Connector

IP Rating: IP 66, Wet Location

Weight: 1' 1.5kg / 4' 6kg

Dimensions: 70.9mmx91.5mmx305mm/1219.2mm

ELV-C1/C4-DW

LED Source: CW/WW

DMX Channel: 3 Beam Angle: 120 °

Max Fixture Runs: 50'@120V/100'@240V Power Consumption: 20W(1')/80W(4')

Total Lumens: 1' 800lm 4' 3200lm

Efficacy (Im/W): 40Im/W

CRI: >80

Finish: Anodized Brushed Aluminum (Black or White - Special Order Only)

Housing: Aluminum; Clear Polycarbonate Lens Cover

地址:广州市番禺区石县镇海涌路109号 传真:+86 20 39966398/39966389 邮箱:sales@terbly.com

网站: www.terbly.com

邮箱: sales@terbly.com

Operating Temperature: -20 ° C ~ 45 ° C

Operating Voltage: 100-277V

Dimming: DMX 512

Fixture Connectors: Integral, 8 Pin Male & Female Connector

Rating: IP 66

Weight: 1' 1.5kg / 4' 6kg

Dimensions: 70.9mmx91.5mmx305mm/1219.2mm