

LED WASH LPAR7QZ



产品参数

OPTICS

Source: 7x 35W RGBW high power LEDs

Life: >50,000H

COLORS

RGBW color mixing

Color temperature linear: 2700K to 8000K
Color temperature presets: 2700K, 3200K, 4300K, 5600K, 6500K, 8000K
Excellent color mixing and rainbow effect

FEATURES

Zoom range: 7 ° -35 ° (Beam Angle), 10 ° -50 ° (Field Angle)
Strobe: electronic, variable from 1-25Hz or pulse
Dimmer: 0%-100% linear dimming
Ring control
GAMMA: 2.0, 2.2, 2.4, 2.6, 2.8, to fit different camera s'linearity
Refresh rate: 900Hz - 24,000 Hz

DISPLAY

Battery operated for fast addressing
15 second standby auto lock
Pan/ Tilt disengage (hold MENU and ENTER button)

SOFTWARE

Upgrades: fast and convenient with uploader over DMX
Remote reset DMX address, fixture reset, sound control by DMX
Run time of LED engine and fixture
4 DMX channel Mode: 6/10/18/28 channels

3 Operational modes: DMX-512, Master/Slave & Sound Active

OTHER SPEC

Input signal isolation

Optional installed wireless receiver

RDM compatible

POWER

Input voltage: AC100 – 240V, 50/60 Hz

DIMENSION AND WEIGHT

Packing Dimension: 43.5X37X36.5cm

Net Weight: 5kg

Gross Weight: 9kg