

NA3FDM

XLR female-male feedthrough adapter for panel mount



Technical Information [hide](#)

Product	
Title	NA3FDM
Connection Type	Adapter
Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 5 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	16 A
Rated voltage	< 50 V
Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm ²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock
Chassis shape	D
Material	
Contact plating	2 μm Ag over 2 μm Ni
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67

[Home](#)
[Products](#)
[About us](#)
[Contact](#)
[Support](#)
[List \(ZnAl4Cu1\)](#)

Shell plating	Nickel
---------------	--------

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

Accessories

SCCD-W



SCDX

