

NAC3FCB

Lockable cable connector, power-out, screw terminals, grey

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

Attention: The powerCON is a connector without breaking capacity, i.e. the powerCON should not be connected or disconnected under load or live!



Features & Benefits

- Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating
- Fast and easy twist lock latching system
- Extremely robust and reliable
- Ergonomic design
- Unique Neutrik chuck type strain relief
- Improved kink protection by two-component bushing
- UL, cUL recognized components
 - VDE certified
 - SEV approved
- Branded with unique hologram - guarantees genuine and authentic Neutrik product

Image gallery



Technical Information [hide](#)

Product	
Title	NAC3FCB
Gender	female
Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	> 0.1 GΩ (after damp heat test IEC 68-2-30)
Number of electronical contacts	2 + PE
Rated current per contact	20 A rms
Rated voltage	250 V ac
Mechanical	
Cable O.D.	6 - 15 mm (1)
Lifetime	> 1000 mating cycles
Wiresize	2,5 mm ²
Wiresize	14 AWG
Home	Products
About us	Contact
Support	

Locking device	Quick Lock
(1)	Cable O.D. range limited to 6 mm - 14 mm acc. VDE
Material	
Contact plating	4 µm Ag
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	Polyamide (PA 6 30 % GR)
Strain relief	Polyacetal (POM)
Environmental	
Temperature range	-30 °C to +80 °C
Product specific	
Coding	B-type for power outlet (color coding gray)

Accessories**HTFAC**