

NBLC75BVZ17

The rearTWIST HD Large BNC cable connector is designed for large cable diameters as used on long runs and high data rates (HD).

Like all Neutrik BNCs it offers a true 75 Ω design and is perfectly suitable for HD applications. The patented rearTWIST boot guarantees easy access even in high density applications.

Suitable cables:

Belden 7731A (ANH), CAE HD16720LSZH, Draka 1.6/7.3AF, RG 11, Klotz V16/72, Canford SDV-HD, Nexans HF 75 1,6/7,2 02Y(ST)C(ST)H, Percon VK9, Tesca Sphere

Crimp size:

Pin: 1.8 mm

Shield: 10.0 mm (hex)

Features & Benefits

- "rearTWIST Principle" locking/unlocking using the easily accessible soft touch boot (Patent DE 100 48507)
- Ideal for recessed bulkheads where access to the "head" of the connector might be an issue. These connectors turn from the back and not the front.
- True 75 Ω design meets the stringent HDTV / DVD requirements
- Leading area: Avoids tilting due to side forces to protect contacts from deformation. Guarantees a lifetime of min. 1000 mating cycles!
- Snug-fit center pin insert provides tactile feedback
- Shield and jacket crimp technology prevents the problem of an exposed grounding braid on cable assemblies
- Excellent cable protection and retention
- Precise Swiss machined brass parts for outstanding durability
- Accessories include crimp tool and dies



Image gallery



Technical Information [hide](#)

Product

Title NBLC75BVZ17

Connection Type BNC 75 Ω

Gender male

Electrical

Contact resistance ≤ 3 m Ω (inner)

Contact resistance ≤ 2 m Ω (outer)

Dielectric strength 1,5 kVdc

Impedance 75 Ω

Insulation resistance > 5 G Ω

Rated voltage < 50 V

≤1.050/>32 dB up to 1 GHz
 ≤1.065/>30 dB up to 2 GHz
 ≤1.100/>26 dB up to 3 GHz

Mechanical

Cable O.D.	10.4 mm
Cable retention	> 30 N (Center)
Crimp size	10.0 mm (HEX)
Crimp size (pin)	1.8 mm
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Locking device	Bayonett
Cable anchoring	Jacket crimping

Material

Contacts	Brass (CuZn35Pb2), 0.2 µm AuCo (Center contact)
Insert	PTFE
Shell	Brass (CuZn39Pb3)
Shell plating	Optalloy®

Environmental

Temperature range	-30 °C to +85 °C
Contact crimpability	Complies with IEC 60803 and IEC 60352-2

Accessories

BST-BLC-CY



CAS-BNC-T

HX-R-BNC

CS-BNC-LCV



DIE-R-BNC-ZPLUS

