

NLT4FX

4 pole female cable connector, nickel housing, chuck type strain relief

The speakON STX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STX Series features an all metal housing.



Features & Benefits

- Current rating 40 A continuous, 50 A audio signal with 50% duty cycle
- Robust and durable all metal housing
- Sealing ring provides weatherproof IP54 rating in mated condition
- Reinforced metal quick lock system for ease and precise locking
- Extra large solder contacts for up to 6 mm² (AWG 10) wires
- Mate with all available speakON products

Technical Information [hide](#)

Product				
Title	NLT4FX			
Connection Type	speakON			
Gender	female			
Electrical				
Contact resistance	< 2 mΩ (after lifetime)			
Dielectric strength	4 kVdc (peak)			
Insulation resistance	> 10 GΩ			
Rated current per contact	40 A rms continuous			
Rated current per contact	50 A audiosignal, duty cycle 50 %			
Rated voltage	250 V (Insulation)			
Attention	speakON is NOT to be used as an AC mains or power supply connector!			
Mechanical				
Cable O.D.	9 - 16 mm			
Cable retention	≥ 220 N (subject to cable O.D. and material)			
Lifetime	> 5000 mating cycles			
Wiresize	6 mm ²			
Wiresize	10 AWG			
Wiring	Solder contacts			
Locking device	Quick Lock (latch)			
Home	Products	About us	Contact	Support

Material

Contact plating	4 µm Ag
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	Zinc diecast (ZnAl4Cu1)
Strain relief	Polyacetal (POM)

Environmental

Flammability	UL 94 HB
Protection class	IP 54 (mated condition)
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C